



MLAIC

Small Arms Committee Report

Email: sac@mlaic.com

Web: <http://mlaic.org/approved-makers-firearms/>

Inquiry data:

Name	Gerhard Lang
Date	21.03.2022
Email	SG@MLAIC.ORG
Discipline	Lamarmora, Minie
Rep. No.	

Decision:

	Date	Approval	
		Yes	No
SAC	31.05.2022	Yes	
Commission	01.07.2022	Yes	
SG	02.07.2022	Yes	

Question

Where on the barrel of the reproduction Mauser Württemberger M1857 should the rear sight be positioned and how may it be reattached to the barrel if it has to be moved?

Remarks

Measurement C : length between the end of the barrel and the extreme rear part of the sight (when lowered) is 81 mm (+13 mm, as -13 mm is not applicable due to the octagonal shape of the barrel where it is not possible to move further backwards!); i.e. 81 to max. 94 mm from the end of the barrel as per photo.

Measurement D : length between the end of the barrel and the front line of the sight socket (base) is 150 mm (+13 mm, as -13 mm is not applicable due to the octagonal shape of the barrel where it is not possible to move the sight further backwards!); i.e. 150 to max. 163 mm from the end of the barrel as per photo.

The method of fixing the rear sight on the barrel when necessary to move it backward.

Soft soldering and gluing will be accepted by MLAIC although it is not the original way of fixing the rear sight of that firearm (the originals were apparently fixed by hard soldering).

Pictures attached to original question



